

Buoyancy Guideline

| Product | Depth rating, m | Density, kg/m ³ | Format, mm | | | Volume, ltr. | *Net buoyancy, kg |
|----------|--------------------|-------------------------------|------------|-------|-----------|--------------|----------------------|
| | | | Length | Width | Thickness | | |
| HCP 30 | 250 | 200 | 1730 | 850 | 50 | 73,5 | 60,7 |
| HCP 50 | 300 | 250 | 1640 | 800 | 50 | 65,6 | 50,8 |
| HCP 70 | 400 | 300 | 1410 | 700 | 30 | 29,6 | 21,5 |
| HCP 90 | 450 | 360 | 1360 | 670 | 27 | 24,6 | 16,4 |
| HCP 100 | 550 | 400 | 1330 | 650 | 23 | 19,9 | 12,4 |
| SF 1100 | 1100 | 445 | 950 | 400 | 150 | 57 | 33,1 |
| CF 2000 | 2000 | 530 | 950 | 400 | 150 | 57 | 28,2 |
| S60 | 2000 | 600 | 1000 | 1000 | 125 | 130 | 55 |
| SF 3000 | 3000 | 495 | 950 | 400 | 150 | 57 | 30,2 |
| S63 | 3000 | 630 | 1000 | 1000 | 125 | 130 | 51 |
| SF 3600 | 3600 | 515 | 950 | 400 | 150 | 57 | 29,1 |
| SF 4500 | 4500 | 545 | 950 | 400 | 150 | 57 | 27,4 |
| SF 8000 | 8000 | 710 | 950 | 400 | 150 | 57 | 18,0 |
| LD 1000 | 1000 | 390 | 950 | 400 | 90 | 34,2 | 21,7 |
| TG24 | 2000 | 385 | 300 | 300 | 150 | 13,5 | 8 |
| S40 | 2000 | 403 | 750 | 500 | 150 | 60 | 37,3 |
| LD 2000 | 2000 | 425 | 950 | 400 | 125 | 47,5 | 28,5 |
| TG26 | 3000 | 416 | 300 | 300 | 150 | 13,5 | 7,4 |
| S45 | 3000 | 436 | 750 | 500 | 150 | 60 | 35,5 |
| LD 3000 | 3000 | 450 | 950 | 400 | 125 | 47,5 | 27,3 |
| TG28 | 4000 | 448 | 300 | 300 | 150 | 13,5 | 7 |
| LD 6000 | 6000 | 570 | 950 | 400 | 150 | 57 | 25,9 |
| LD 8000 | 8000 | 635 | 950 | 400 | 140 | 53,2 | 20,7 |
| LD 10000 | 10000 | 695 | 950 | 400 | 110 | 41,8 | 13,8 |

*Based on net weight sea water = 1025 kg/m³.